

Basic Telephone Entry

TEC101

STANDARD FEATURES:

- TWO RELAYS**
- NO SUNSHIELD NEEDED TO READ LCD DISPLAY**
- LCD DISPLAY BACKLIT FOR NIGHT VIEWING**
- BOARD LEVEL SURGE PROTECTION**
- TRANSFORMER INCLUDED**
- PROGRAMMABLE VIA KEYPAD OR WITH OPTIONAL
MODEM AND SOFTWARE**
- DISPLAY WORKS IN COLD OR HOT WEATHER:
-0F to +158F**
- WEATHER RESISTANT HOUSING**
- TWO YEAR LIMITED WARRANTY ***



TEC101 Shown with Nite Lite Hood on pedestal.

OPTIONS:

- 300 - 1200 BAUD MODEM
WITH COMPLEMENTARY SOFTWARE
(Software now Isolated and Protected)**
- NITE LITE WEATHER HOOD**
- SEMI FLUSH MOUNT RING**
- MUI: MULTI UNIT INTERFACE**
- NO PHONE BILL SYSTEM:
ALLIANCE 2002**
- PEDESTALS AND MOUNTING PLATE**

The TEC101 provides basic telephone entry with the SES advantage. TEC101 is offered in four capacities: 50, 125, 500 and 995 to match your requirements. All are offered with 2 relays standard and have a two line LCD directory display that is easily read in direct sunlight or at night. As with all SES telephone access systems, the TEC101 has board level surge suppression at no additional cost, and the stainless steel front door and aluminum back box is sure to provide years of faithful service. The TEC101 has a two year limited warranty, and is designed to the same standards as the TEC and CAT product lines.

TEC101, the best of basic telephone entry, with SES quality.

"Select...Don't Settle"



ACCESS CONTROL

FEATURES

- TEC101 is offered in four capacities 50, 125, 500 and 995. Each offers the same number of phone numbers, PIN codes and names.
- 1 to 6 digit directory code length, programmable.
- Surge protection is integrated on all inputs and outputs, to minimize adverse effects of transient voltages.
- Personal Identification Number (PIN code) for resident entry is from 1 to 6 digits, programmable.
- Voice mail response capability via active keypad, programmable.
- Hide a name feature, programmable.
- Two door control relays.
- Dials out touch tone or rotary.
- Will not accept touch tone through the microphone.
- Mutes tones in speaker while dialing.
- Fully programmable through the keypad.
- Dials up to 14 digit telephone numbers.
- Two line LCD display, provides directory names one at a time.
- Talk time programmable from 1- 99 minutes.
- Postal lock capability included.
- Request to exit inputs for both entrance control relays.
- Entry code attempts (strike out) is programmable from 0 to 9.
- Non-volatile memory.
- Surface or pedestal mounting.
- Remote door release through telephone touch tone.
- Programmable background "beep" to indicate incoming call was from TEC101.
- Manager Password.
- Battery charging circuit.
- 2 year limited warranty.

SPECIFICATIONS

- Outside dimensions:
8 1/2"W x 11 3/4"H x 3 1/2"D
- Shipping weight: Approx. 11 lbs.
- Power: 16.5VAC 20VA transformer (supplied).
- Construction: stainless steel front door, with aluminum back box.
- Operating environment:
Temperature: - 0F to 158F
Relative humidity: 5% to 95% non-condensing
- Memory type: non-volatile
- Relay output: Form A or B dry contact 24 V @ 3 AMPS.
- Tone detection: crystal controlled, will detect short burst 50 ms tone.

OPTIONS

- 300 -1200 baud modem with complementary software.
- MUI, Multi Unit Interface: (allows up to 4 TEC1's on one phone line).
- Pin hole camera: B & W or color.
- Nite Lite weather hood.
- Standard weather hood.
- Semi-flush mount ring.
- Back box stainless sleeve.
- Handset (specify length).
- Standby battery.
- Pedestals and adapter.
- No phone bill system:
Alliance 2002

APPLICATIONS

- Apartment buildings.
- Small gated communities.
- Condos.
- Office buildings.

"Select...Don't Settle"



0704