



Select Pass and **Multi Pass** products are a line of individually coded, rolling code transmitters and receiver products. Both products are available with 2 or 4 buttons.

The two and four button transmitters are small key chain size. The lightweight, contoured design fits easily into your hand and is convenient to put into a pocket or purse. Powered by replaceable internal CR-type lithium batteries that have a long life expectancy. Devices automatically stops transmitting if a button is held down too long.

The two families of transmitters include:

Select Pass (RTSP) an RF transmitter only. (Polypropylene case)

Multi-Pass (RTMP) an RF transmitter with “**HID Proximity**” inside. (Polypropylene case)

Select Pass (RTSPX2 or RTSPX4) an RF transmitter only.

(Combination metal and polypropylene case)

Multi-Pass (RTMPX2 or RTMPX4) an RF transmitter with “**HID Proximity**” inside.

(Combination metal and polypropylene case)

Imagine the convenience of having a single device with two technologies providing a user with access control that works seamlessly. With **Multi-Pass** you can open the gate with the RF transmitter, and the club house door with the proximity. The Multi-Pass transmitter and proximity coil are programmed with the same code number making database management simple and efficient.

The **Select Pass Receivers** are available in two types, Wiegand output, or a self learning stand alone with relay output.

SELECT PASS / MULTI-PASS

FEATURES

Transmitters: Select pass / Multi pass

- ◆ Rolling code technology prohibits the device number from being copied for better security.
- ◆ Transmitters are individually coded devices interfacing with a frequency matched receiver. For use with any standard Wiegand access control system.
- ◆ Transmitter range is nominally 100 feet.
- ◆ Lithium battery powered.
- ◆ Batteries are readily available and easily replaceable.
- ◆ Built in activation light confirms transmitter actuation.
- ◆ 2 second transmission time limit for each activation extends battery life.
- ◆ Light weight, key chain size, space age design.
- ◆ Recessed button design reduces accidental activation and allows easy operation even with long finger nails or large hands.

Multi pass:

- ◆ Additional features
- ◆ HID proximity tag built in.
- ◆ The HID proximity tag and the RF transmitter are programmed to the same output code for simple data management.

Receiver types:

- ◆ 26-bit Wiegand output.
- ◆ Stand alone self learning with relay output.

APPLICATIONS

- ◆ Gated communities or commercial use.
- ◆ Apartment building access.
- ◆ Condominium access.
- ◆ Townhouses.
- ◆ Retirement homes / Convalescent homes.
- ◆ Residential gates and garages.
- ◆ SES Select Gate SG3DMR with built-in receiver.

SPECIFICATIONS

Transmitters: RTSP — RTMP Rolling code

- ◆ **Material used:** High impact, fracture resistant plastic.
- ◆ **Output:** Radio frequency rolling code @ 433 MHz for 2 seconds max.
- ◆ **Memory type:** Non-volatile EE prom.

RTSP1 (one button) / RTSP2 (two button)

- ◆ **Size:** 1½" x 2 5/16" x ½"
- ◆ **Weight:** 1 oz.
- ◆ **Power:** Batteries Two 3 volt Lithium batteries.

With HID proximity:

- ◆ **Weight:** 1 oz.
- ◆ **HID Proximity insert:**
- ◆ **Power:** none required for prox coil.
- ◆ **Memory Type:** Non-volatile EE prom.

Transmitters: RTSPX — RTMPX Rolling Code (one-two or four button)

- ◆ **Material used:** Metal frame and polypropylene plastic.
- ◆ **Output:** Radio frequency rolling code @ 433 MHz for 2 seconds max.
- ◆ **Memory type:** Non-volatile EE prom.
- ◆ **Size:** 2" x 1 1/4" x ½"
- ◆ **Power:** Single CR-type lithium cell.

With HID proximity:

- ◆ **Weight:** 1.5 oz.
- ◆ **HID Proximity insert:**
- ◆ **Power:** none required for prox coil.
- ◆ **Memory Type:** Non-volatile EE prom.

Receiver: Rolling code / Super-heterodyne.

- ◆ **Construction:** High impact, fracture resistant plastic.
- ◆ **Power Input:** 12/24 VAC or VDC.
- ◆ **Mounting:** Protected area needed.
- ◆ **Operating temperature:** -59°F to +130°F (-15°C to +55°C)

RHRFSPWV2 (Wiegand output)

- ◆ **Size:** 5½" x 4 1/3" x 1 5/8"
- ◆ **Weight:** 8 oz.

RHRFSP20 (self learning stand alone)

- ◆ **Size:** 4" x 2¼" x 1"
- ◆ **Memory:** 20 codes
- ◆ **Weight:** 5 oz.
- ◆ **Relay Output:** Form "C" dry contact

Note:

Products covered under FCC I.D. numbers: ON3MPER2B, ON3MPSDT2, ON3MRRE, ON3TXPRQ2.